Fast Facts

Temperature sensor for heavy duty applications

With a temperature measuring range of -40 °C up to 140 °C and an analog-continuous signal this sensor provides the perfect solution for mobile and industrial applications in temperature measurement. Having most robust and compact design it can be used in nearly all positions. That combination of used materials is especially dedicated to measure fluids. Proven design provides fastest response performance available in the market combined with an AK2.8 connector.

Special Features

- Wide temperature range -40 °C … 140 °C
- Sensing element: resistor with NTC characteristic (2kΩ @25 °C)
- Electrical interface: analog signal (resistance)
- Mechanical interface M14 x 1.5-6g male thread
- RoHS / REACH compliant (Pb-free accord. to techn. rules)
- Integrated connector AK2.8 (IP6K9K)
- Brass and stainless steel housing available

Typical Applications

- Agriculture, heavy duty and industry
- Easy handling with screw-in fixation (fluids like e.g. coolant, different oils)
- Harsh environments (e.g. axle gear of vehicles)



General Note This datasheet does not give any information on product availability. The information given is just meant to describe the product and is not to be considered as guaranteed characteristics in the legal sense. All products are subject to design changes in the interest of further technical development. Copyright: KYOCERA AVX Components (Dresden) GmbH (GER)
www.kyocera-avx.com